

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A61K 7/42, 7/48</b>	<b>A1</b>	(11) International Publication Number: <b>WO 98/00098</b> (43) International Publication Date: <b>8 January 1998 (08.01.98)</b>
<p>(21) International Application Number: <b>PCT/EP97/02958</b></p> <p>(22) International Filing Date: <b>30 May 1997 (30.05.97)</b></p> <p>(30) Priority Data: <b>60/020,746</b>      <b>28 June 1996 (28.06.96)</b>      <b>US</b></p> <p>(71) Applicant (for AU BB CA GB GH IE IL KE LC LK LS MN MW NZ SD SG SZ TT UG only): <b>UNILEVER PLC (GB/GB); Unilever House, Blackfriars, London EC4P 4BQ (GB).</b></p> <p>(71) Applicant (for all designated States except AU BB CA GB GH IE IL KE LC LK LS MN MW NZ SD SG SZ TT UG): <b>UNILEVER N.V. (NL/NL); Weena 455, NL-3013 AL Rotterdam (NL).</b></p> <p>(72) Inventors: <b>CROTTY, Brian, Andrew; 46 Damascus Road, Branford, CT 06405 (US). ZNAIDEN, Alexander, Paul; 110 Fox Road, Trumbull, CT 06611 (US). JOHNSON, Anthony, William; 211 Papermill Lane, Fairfield, CT 06430 (US).</b></p> <p>(74) Agent: <b>ROTS, M., J., F.; Unilever plc, Patent Division, Colworth House, Sharnbrook, Bedford MK44 1LQ (GB).</b></p>		<p>(81) Designated States: <b>AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</b></p> <p><b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: <b>SELF-TANNER COSMETIC COMPOSITIONS</b></p> <p>(57) Abstract</p> <p>A self-tanning cosmetic product is provided for imparting a natural-appearing tan to skin. Besides the self-tanning agent, compositions of this invention will include a crosslinked non-emulsifying siloxane elastomer and a volatile siloxane.</p>		

increase speed of coloration and achieve a coloration even closer to a natural tan.

5 Accordingly, it is an object of the present invention to provide a method and composition for self-tanning having improved rates of coloration, reduced streaking and imparting a more natural hue.

10 A further object of the present invention is to provide a method and composition for self-tanning which utilizes ingredients that impart good aesthetics and have an impeccable health safety profile.

15 Yet another object of the present invention is to provide a self-tanning composition which in emulsion form is stable for long term storage without phase separation.

20 Still another object of the present invention is to provide a composition for self-tanning which in emulsion form achieves a smooth emulsion break when rubbed into the skin.

Still another object of the present invention is to provide a composition for self-tanning which has improved skinfeel properties.

These and other objects of the present invention will become more readily apparent through the following summary, detailed discussion and Examples which follow.

#### SUMMARY OF THE INVENTION

self-tanning composition is provided which includes:

from 0.1 to 40% of a self-tanning agent;

- 3 -

(ii) from 0.1 to 30% of a crosslinked non-emulsifying siloxane elastomer; and

(iii) from 10 to 80% of a volatile siloxane.

5

#### DETAILED DESCRIPTION OF THE INVENTION

Now it has been discovered that a very rapid self-tanning with reduced streaking, improved color intensity and tone can be accomplished by delivering to the skin a self-tanning agent in combination with a crosslinked non-emulsifying siloxane elastomer and a volatile siloxane. Moreover, the composition can be formed into a highly stable emulsion. Improved skinfeel properties are also achieved with this combination of components.

Accordingly, a first essential element of the present invention is that of a self-tanning agent, especially a  $C_3$ - $C_{24}$  alpha-hydroxy alcohol or aldehyde in an amount from 0.1 to 40%, preferably from 1 to 20%, optimally between 2 and 15% by weight of the composition. The alpha-hydroxy alcohol or aldehyde is preferably selected from dihydroxyacetone, glucose, xylose, fructose, reose, ribose, pentose, arabinose, allose, tallose, altrose, mannose, galactose, lactose, sucrose, erythrose, cyclodextrin, glyceraldehyde and combinations thereof. Most preferred is dihydroxyacetone.

Crosslinked non-emulsifying siloxane elastomers are the second essential element of this invention. They will usually have an average number molecular weight in excess of 2,000, preferably in excess of 1,000,000. Typically they will range from 10,000 to 20 million. The term "non-emulsifying" defines a siloxane from which polyoxyalkylene units are absent. Advantageously the elastomers are

5 formed from a divinyl monomer reacting with Si-H linkages  
of a siloxane backbone. Suitable elastomer compositions  
are commercially available from the General Electric  
Company under product designation General Electric  
10 Silicone 1229 with proposed CTFA name of Cyclomethicone  
and Vinyl Dimethicone/Methicone Cross Polymer, delivered  
as 20-35% elastomer in a cyclomethicone carrier. A  
related elastomer composition under the CTFA name of  
Crosslinked Stearyl Methyl Dimethyl Siloxane Copolymer is  
15 available as Gransil SR-CYC (25-35% elastomer in  
cyclomethicone) from Grant Industries, Inc., Elmwood Park,  
New Jersey. The commercial products from General Electric  
and Grant Industries preferably are further processed by  
subjecting them to a high pressure (approximately 5,000  
20 psi) treatment in a Sonolator with recycling in 10 to 60  
passes. Sonolation achieves a resultant fluid with  
elastomer average particle size ranging from 0.2 to 10  
micron, preferably 0.5 to 5 micron. Viscosity is best  
when ranging between 300 and 20,000 cps at 25°C as measured  
by a Brookfield LV Viscometer (size 4 bar, 60 rpm, 15  
sec.).

25 Amounts of the elastomer may range from 0.1 to 30%,  
optimally from 1 to 15%, most preferably from 3 to 10% by  
weight.

30 A third essential element to be incorporated into the  
compositions of this invention is that of a volatile  
siloxane. This material may be present in amounts from 10  
to 80%, preferably from 20 to 60%, optimally from 30 to  
50% by weight.

35 The term "volatile" refers to those materials having a  
measurable pressure at ambient conditions. Volatile  
polyorganosiloxanes useful herein may be cyclic or linear.  
Preferred cyclic silicones include polydimethylsiloxanes

- 5 -

containing from about 3 to about 9 silicon atoms,  
preferably containing from about 4 to about 5 silicon  
atoms, generally known as cyclomethicones. Preferred  
linear silicone oils include the polydimethylsiloxanes  
5 containing from about 3 to about 9 silicon atoms. The  
linear volatile silicones generally have viscosities of  
less than about 5 centistokes at 25°C, while the cyclic  
materials have viscosities of less than about 10  
centistokes, the preferable range being from 0.1 to 8  
10 centistokes. Examples of silicone oils useful in the  
present invention include: Dow Corning 244, Dow Corning  
245, Dow Corning 344, Dow Corning 345 and Dow Corning 200  
(manufactured by the Dow Corning Corporation); Silicone  
7207 and Silicone 7158 (manufactured by the Union Carbide  
15 Corporation); SF1202 (manufactured by General Electric).

Humectants may also be included as components of  
compositions according to the present invention. These  
humectants are polyhydric alcohols intended for  
20 moisturizing, reducing scaling and stimulating removal of  
built-up scale from the skin. Most important for the  
present invention, the polyhydric alcohols enhance skin  
colorization of the self-tanning agent. Typical  
polyhydric alcohols include polyalkylene glycols and more  
25 preferably alkylene polyols and their derivatives.  
Illustrative are propylene glycol, dipropylene glycol,  
polypropylene glycol, polyethylene glycol, sorbitol,  
hydroxypropyl sorbitol, hexylene glycol, 1,3-butylene  
glycol, 1,2,6-hexanetriol, glycerin, ethoxylated glycerin,  
30 propoxylated glycerin and mixtures thereof. Most  
preferably the humectant is glycerin. Amounts of  
humectant may range anywhere from 1 to 50%, preferably  
from 10 to 40%, optimally from 25 to 35% by weight.

35 Another optional component is that of an emollient which  
may be selected from hydrocarbons or esters. Petrolatum

- 6 -

is the most preferred emollient conditioning agent. Other hydrocarbons that may be employed include mineral oil, polyolefins such as polydecene, and paraffins such as isohexadecane (e.g. Permethyl 99® and Permethyl 101®).

5

Ester emollients may be those selected from one or more of the following classes:

- 10 1. Triglyceride esters such as vegetable and animal fats and oils. Examples include castor oil, cocoa butter, safflower oil, cottonseed oil, corn oil, olive oil, cod liver oil, almond oil, avocado oil, palm oil, sesame oil, squalene, Kikui oil and soybean oil.
- 15 2. Acetoglyceride esters, such as acetylated monoglycerides.
- 20 3. Ethoxylated glycerides, such as ethoxylated glyceryl monostearate.
- 25 4. Alkyl esters of fatty acids having 10 to 20 carbon atoms. Methyl, isopropyl, and butyl esters of fatty acids are useful herein. Examples include hexyl laurate, isohexyl laurate, isohexyl palmitate, isopropyl palmitate, decyl oleate, isodecyl oleate, hexadecyl stearate, decyl stearate, isopropyl isostearate, diisopropyl adipate, diisohexyl adipate, dihexyldecyl adipate, diisopropyl sebacate, lauryl lactate, myristyl lactate, and cetyl lactate.
- 30 5. Alkenyl esters of fatty acids having 10 to 20 carbon atoms. Examples thereof include oleyl myristate, oleyl stearate, and oleyl oleate.
- 35 6. Ether-esters such as fatty acid esters of ethoxylated fatty alcohols.

- 7 -

7. Polyhydric alcohol esters. Ethylene glycol mono and di-fatty acid esters, diethylene glycol mono-and di-fatty acid esters, polyethylene glycol (200-6000) mono- and di-fatty acid esters, propylene glycol mono- and di-fatty acid esters, polypropylene glycol 2000 monooleate, polypropylene glycol 2000 monostearate, ethoxylated propylene glycol monostearate, glyceryl mono- and di-fatty acid esters, polyglycerol polyfatty esters, ethoxylated glyceryl monostearate, 1,2-butylene glycol monostearate, 1,2-butylene glycol distearate, polyoxyethylene polyol fatty acid ester, sorbitan fatty acid esters, and polyoxyethylene sorbitan fatty acid esters are satisfactory polyhydric alcohol esters.

8. Wax esters such as beeswax, spermaceti, myristyl myristate, stearyl stearate.

20 Cosmetic compositions of the present invention may either be anhydrous or aqueous emulsions. When anhydrous, the amount of water will be confined to range from 0 to 5%, preferably not above 2%, optimally not above 0.5% by weight. When the compositions of this invention are in emulsion form, the amount of water will usually range from 5 to 50%, preferably from 7 to 30%, optimally from 10 to 20% by weight. The emulsions may be of the oil-in-water, water-in-oil or duplex variety. Aqueous to oily phases can range in weight from 10:1 to 1:10, preferably from 1:1 to 1:5, optimally from 1:1 to 1:2.

Most preferable for the present invention are water-in-oil emulsions having a low internal (water) phase volume. These emulsions will normally consist essentially of self-tanning agent, elastomer, polyhydric alcohol, cyclomethicone and water. Anhydrous systems optimally

- 8 -

will consist essentially of self-tanning agent, elastomer, petrolatum and cyclomethicone.

- 5 Beyond the basic components, other materials may be included depending upon the particular type of cosmetic composition sought. For instance, surfactants may be formulated into the compositions. These may be selected from nonionic, anionic, cationic or amphoteric emulsifying agents. They may range in amount anywhere from about 0.1 to about 20% by weight. Illustrative nonionic surfactants are alkoxyated compounds based on C<sub>10</sub>-C<sub>22</sub> fatty alcohols and acids, and sorbitan. These materials are available, for instance, from the Shell Chemical Company under the Neodol trademark. Copolymers of polyoxypropylene-  
10 polyoxyethylene, sold by the BASF Corporation under the Pluronic trademark, are sometimes also useful. Alkyl polyglycosides available from the Henkel Corporation may also be utilized for purposes of this invention.
- 15
- 20 Anionic type surfactants include fatty acid soaps, sodium lauryl sulphate, sodium lauryl ether sulphate, alkyl benzene sulphonate, mono- and di-alkyl acid phosphates and sodium fatty acyl isethionate.
- 25 Amphoteric surfactants include such materials as dialkylamine oxide and various types of betaines (such as cocoamidopropyl betaine).
- 30 Preservatives can desirably be incorporated into the compositions of this invention to protect against the growth of potentially harmful microorganisms. While it is in the aqueous phase that microorganisms tend to grow, microorganisms can also reside in the oil phase. As such, preservatives which have solubility in both water and oil are preferably employed in the present compositions.
- 35 Suitable traditional preservatives are hydantoin



- 9 -

derivatives, propionate salts, and a variety of quaternary ammonium compounds. Cosmetic chemists are familiar with appropriate preservatives and routinely choose them to satisfy the preservative challenge test and to provide product stability. Particularly preferred preservatives are methyl paraben, propyl paraben, imidazolidinyl urea, sodium dehydroxyacetate and benzyl alcohol. The preservatives should be selected having regard for the use of the composition and possible incompatibilities between the preservatives and other ingredients. Preservatives are preferably employed in amounts ranging from 0.01% to 2% by weight of the composition.

Minor adjunct ingredients may also be included such as fragrances, antifoam agents, opacifiers and colorants, each in their effective amounts to accomplish their respective functions.

The following examples will more fully illustrate the embodiments of this invention. All parts, percentages and proportions referred to herein and in the appended claims are by weight unless otherwise indicated.

#### 25 EXAMPLE 1

This Example illustrates an anhydrous skin tanning composition. Components listed in the Table below are added together in a vessel at 60°C and mixed with a homogenizing agitator. Thereafter they are subjected to sonolation at 800-1,000 psi for five to ten minutes. The resultant product is a non-greasy semi-solid with a very silky afterfeel and excellent self-tanning properties.

35

TABLE I

COMPONENT	WEIGHT%
Petrolatum	18.5
GE 1229	30
DC 344 Fluid®	41.5
Dihydroxyacetone	10

**EXAMPLE 2**

A water-in-oil emulsion of low internal phase is prepared in a manner similar to that of Example 1. The resultant tanning product will be fluid and highly penetrating when rubbed into the skin. It will exhibit an excellent smooth, silky afterfeel. The product will tan skin in a uniform, non-streaking manner.

TABLE II

COMPONENT	WEIGHT %
Glycerin	20
GE 1229	20
Water	12
DC 244 Fluid®	40
Dihydroxyacetone	8

**EXAMPLE 3**

This Example illustrates another anhydrous skin tanning composition according to the present invention. The formulation may be prepared in a manner essentially similar to that of Example 1 utilizing the components

- 11 -

listed in the Table below. The resultant product will have a smooth, silky afterfeel and impart a tan of excellent color.

**TABLE III**

COMPONENT	WEIGHT %
Petrolatum	22
Gransil SR-CYC	43
DC 244 Fluid®	33
Cyclodextrin	2

**EXAMPLES 4-12**

Illustrated in the Table below are a series of anhydrous and aqueous self-tanning emulsion formulations according to the present invention. These examples can be prepared in a manner similar to that described in Example 1.

**TABLE IV**

COMPONENT	EXAMPLE NO. (WEIGHT %)									
	4	5	6	7	8	9	10	11	12	
Dihydroxyacetone	5	10	15	10	10	10	2	20	30	
Petrolatum	2	10	45	--	--	--	--	10	10	
Isohexadecane	18	10	--	--	--	--	--	--	--	
Glycerin	--	--	--	10	--	--	8	--	10	
Propylene Glycol	--	--	--	--	10	--	--	--	--	
Polyethylene Glycol	--	--	--	--	--	10	--	--	--	
Crosslinked Siloxane Elastomer	30	20	10	10	10	10	10	15	20	
Water	--	--	--	40	40	40	50	40	10	
Cyclomethicone	45	50	30	30	30	30	30	15	20	

**EXAMPLE 13**

Comparative performance characteristics were evaluated for a set of sunless tanner formulations listed in Table V.

**TABLE V**

COMPONENT	EXAMPLE (WEIGHT %)		
	A	B	C
DC 245 Fluid	52.0	52.0	52.0
EM-90	0.75	0.75	0.75
Gransil SR-CYC	8.0	--	--
DC 200 (polydimethylsiloxane)	--	8.0	--
Trasil (cycloethoxymethicone)	--	--	8.0
Propylene Glycol	25.0	25.0	25.0
Water	11.25	11.25	11.25
Dihydroxyacetone	3.0	3.0	3.0

Each of the samples were prepared in a manner similar to that described for Example 1. Sample A was an elegant cosmetic cream. Sample B was a liquid which separated upon standing. Sample C was a slightly viscous liquid which also separated upon standing.

Efficacy was tested by applying equal amounts of each sample over equivalent areas on the arms of a panelist. Approximately 1 cc of each formulation was applied over a 5 cm square area. Intensity, uniformity and tone were assessed after 24 hours. Results are reported in Table VI.

**TABLE VI**

SAMPLE	COLOR INTENSITY	STREAKINESS	COLOR TONE
A	+++++	-	Brown Excellent
B	+	-	Yellow Brown
C	++++	---	Yellow Brown

5  
10

The greater the number of (+) or (-) symbols the larger the respective beneficial or detrimental effect. As can be seen from Table VI, the best combination of properties was seen from Sample A. A very high degree of color intensity was achieved with excellent brown tone and acceptable uniformity. Sample C exhibited a high degree of unacceptable streakiness.

15

CLAIMS

- 5        1.    A self-tanning composition comprising:
- (i)    from 0.1 to 40% of a self-tanning agent;
- (ii)   from 0.1 to 30% of a crosslinked non-  
10                emulsifying siloxane elastomer; and
- (iii)   from 10 to 80% of a volatile siloxane.
- 15        2.    A composition according to claim 1 which is anhydrous.
3.    A composition according to claim 1, further comprising from 5 to 50% by weight of water.
- 20        4.    A composition according to any one of claims 1-3 wherein the crosslinked non-emulsifying siloxane elastomer is formed from a divinyl monomer reacting with Si-H linkages of a siloxane backbone.
- 25        5.    A composition according to any one of claims 1-4 wherein the volatile siloxane is cyclomethicone.
- 30        6.    A composition according to any one of claims 1-5 wherein the self-tanning agent is selected from the group consisting of dihydroxyacetone, glucose, xylose, fructose, reose, ribose, pentose, arabinose, allose, tallose, altrose, mannose, galactose, lactose, sucrose, erythrose, cyclodextrin, glyceraldehyde and combinations thereof.
- 35        7.    A cosmetic composition according to claim 6 wherein the self-tanning agent is dihydroxyacetone.

# INTERNATIONAL SEARCH REPORT

Inter. Appl. No.

PCT/EP 97/02958

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 A61K7/42 A61K7/48

According to International Patent Classification(IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 95 06078 A (PROCTER & GAMBLE) 2 March 1995 see page 38, line 11-14 see page 45, line 1-11 see claims 1,10; example 24 ---	1,4-7
A	CHEMICAL ABSTRACTS, vol. 124, no. 4, 22 January 1996 Columbus, Ohio, US; abstract no. 37399; "Two-layer oily make up cosmetics containing spherical powders of organopolysiloxane elastomers and hydrophobic-treated powders" XP002045552 see abstract & JP 07 267 820 A (SHISEIDO CO LTD) 17 October 1995 --- -/-	1-7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" documents referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

3 November 1997

Date of mailing of the international search report

24/11/1997

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Sierra Gonzalez, M

# INTERNATIONAL SEARCH REPORT

Inter. Appl. Application No  
PCT/EP 97/02958

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 95 22960 A (ESTEE LAUDER INC) 31 August 1995  see page 10, line 26-35  see examples 1-4  see claims 1,8,9  -----</p>	1-7



# INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter. Appl. No.

PCT/EP 97/02958

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9506078 A	02-03-95	AU 7560094 A	21-03-95
		AU 7630994 A	21-03-95
		BR 9407560 A	31-12-96
		BR 9407627 A	21-01-97
		CA 2169087 A	02-03-95
		CA 2169091 A	02-03-95
		CN 1133603 A	16-10-96
		CN 1133604 A	16-10-96
		CZ 9600528 A	12-06-96
		CZ 9600529 A	12-06-96
		EP 0715637 A	12-06-96
		EP 0715638 A	12-06-96
		HU 73653 A	30-09-96
		HU 73651 A	30-09-96
		JP 9501728 T	18-02-97
		JP 9501729 T	18-02-97
		NO 960681 A	23-04-96
		NO 960682 A	22-04-96
		WO 9506079 A	02-03-95
		US 5622694 A	22-04-97
WO 9522960 A	31-08-95	US 5514367 A	07-05-96
		AU 1926295 A	11-09-95